

Narendra

**STRAIGHT
SIDED
SINGLE
POINT
PRESS**



SERIES NSU

Narendra

TECHNICAL SPECIFICATIONS

MODEL		NSU-125	NSU-165	NSU-200	NSU-250	NSU-315	NSU-400	NSU-500	NSU-600	
CAPACITY	TON	125	165	200	250	315	400	500	600	
RATING POINT	MM	5	6	9	12	12	12	12	13	
BOLSTER AREA LR X FB	MM	700X600	900X800	900X800	1000X900	1100X1000	1200X1100	1300X1200	1400X1300	
SLIDE AREA LR X FB	MM	650X550	750X750	800X800	900X900	900X900	1000X1000	1100X1000	1200X1100	
FIXED STROKE	MM	125	160	200	200	250	300	300	300	
DIE HEIGHT	MM	350	400	400	450	500	550	600	700	
SLIDE ADJUSTMENT	MM	90	110	125	125	150	150	200	200	
BOLSTER THICKNESS	MM	140	140	160	180	180	200	200	200	
WINDOW OPENING	MM	300X400	300X400	400X450	400X450	400X450	450X500	500X550	500X600	
FLOOR TO TOP OF BLOSTER	MM	900	900	1000	1000	1050	1100	1100	1100	
AIR PRESSURE	kg/cm ²	5	5	5	5	5	5	5	5	
SPEED	SPM	45	40	35	35	30	25	20	20	
MAIN MOTOR	HP	12.5	15	20	25	30	40	50	60	
SLIDE ADJUSTMENT MOTOR	HP	0.5	0.5	1	1	1	1.5	1.5	1.5	
DIE CUSION (OPT.)	CAPACITY	TON	8	10	14	14	30	40	50	50
	STROKE	MM	80	90	100	100	150	150	150	150

We reserve the right to change, design and modify specification at the discretion of our engineering department

Manufactured and Marketed by:

NARENDRA PRESS TECH PVT. LTD.

P.P. 26, Lane no. 10, Behind Police Station,

Anand Parbat Industrial Estate, New Delhi-110 005, (INDIA)

Ph. : + 91-11-28761468, +91-11-28761467, Fax : +91-11-28761576 .

UNIT - 2

PLOT NO. 65, SECTOR 3, IMT MANESAR, GURGAON, HARYANA (INDIA).

TELEFAX.: 0124 2291354

E-mail : sales@narendrapresstech.com Website : www.narendrapresstech.com